

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/085874 A1

(51) International Patent Classification⁷: **G01N 35/04**,
35/02

(74) Agents: **TAKAMATSU, Takeshi** et al.; Eikoh Patent
Office, 13th Floor, ARK Mori Building, 12-32, Akasaka
1-chome, Minato-ku, Tokyo 1076013 (JP).

(21) International Application Number:
PCT/JP2005/004139

(22) International Filing Date: 3 March 2005 (03.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-061990 5 March 2004 (05.03.2004) JP

(71) Applicant (for all designated States except US): **MAT-
SUSHITA ELECTRIC INDUSTRIAL CO., LTD.**
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka,
5718501 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **HIGUCHI, Akira.**

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: APPARATUS OF SUPPLYING AND CONTAINING MICRO-PLATE, METHOD OF SUPPLYING AND METHOD
OF CONTAINING MICRO-PLATE AND APPARATUS OF PROCESSING MICRO-PLATE



(57) Abstract: It is an object of the invention to provide an apparatus of supplying a micro-plate excellent in operating performance and operability. In a micro-plate supplying apparatus for separating micro-plates 10 mounted in a stacked state sheet by sheet to supply, a first stock portion 2, a second stock portion 3 for containing the micro-plates in the stacked state are arranged in series in an up and down direction by interposing a micro-plate take out and take in mechanism 4, the micro-plates 10 are moved from the first stock portion 2 to the second stock portion 3 while staying in the stacked state, the micro-plate at a uppermost stage of the plurality of micro-plates 10 is disposed at a micro-plate carry out level L2, and the micro-plate is taken out by a micro-plate carrying out mechanism to supply to a working apparatus 5. Thereby, the micro-plate is set in an excellent operation attitude and the micro-plate can stably be taken out.

WO 2005/085874 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*